Trade name: Clear Shield Canvas Guard Satin

Version: 3 / GB Date revised: 09.01.2015

Substance number: 3602XX413 Replaces Version: 2 / GB Print date: 09.08.18

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Clear Shield Canvas Guard Satin

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# Use of the substance/preparation

Liquid laminate

#### **Identified Uses**

PROC10

SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
SU22	Professional uses: Public domain (administration, education, entertainment,
	services, craftsmen)
PROC1	Use in closed process, no likelihood of exposure
PROC2	Use in closed, continuous process with occasional controlled exposure
PROC3	Use in closed batch process (synthesis or formulation)
PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises
PROC5	Mixing or blending in batch processes for formulation of preparations and articles

(multistage and/or significant contact)

PROC8a Transfer of substance or preparation (charging/discharging) from/to vessels/large

containers at non dedicated facilities

PROC8b Transfer of substance or preparation (charging/discharging) from/to vessels/large

containers at dedicated facilities Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring

PROC19 Hand-mixing with intimate contact and only PPE available

ERC4 Industrial use of processing aids in processes and products, not becoming part of

articles

ERC8a Wide dispersive indoor use of processing aids in open systems ERC8d Wide dispersive outdoor use of processing aids in open systems

# Uses advised against

SU21 Consumer uses: Private households (= general public = consumers)

#### 1.3. Details of the supplier of the safety data sheet

#### **Address**

Marabu North America 2460 A Remount Rd. 29406 N. Charleston, SC

Telephone no. 843-886-0094

Information provided Department product safety

by / telephone

E-mail address of PRSI@marabu.de

person responsible

for this SDS

#### 1.4. Emergency telephone number

843-886-0094

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Trade name: Clear Shield Canvas Guard Satin

Version: 3 / GB Date revised: 09.01.2015

Substance number: 3602XX413 Replaces Version: 2 / GB Print date: 09.08.18

Aquatic Chronic 3 H412 Skin Sens. 1A H317

#### 2.2. Label elements

# Labelling according to regulation (EC) No 1272/2008

#### **Hazard pictograms**



#### Signal word

Warning

#### **Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

H317 May cause an allergic skin reaction.

#### **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

#### Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl

1,2,2,6,6-pentamethyl-4-piperidyl

sebacate; Poly[oxy(methyl-1,2-ethanediyl)],a-(methylphenyl)-w-hydroxy; Mixture of alpha-3-(3-(2h-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-h

ydroxypoly(oxyethylene) and alpha-3-(3-(2h-benzotriazol-2-yl)-

5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2h-benzotriazol-2-yl)-5-tert-b

utyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

#### 2.3. Other hazards

No special hazards have to be mentioned.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### **Chemical characterization**

Water containing liquid laminate based on polyurethane

#### **Hazardous ingredients**

### Poly[oxy(methyl-1,2-ethanediyl)],a-(methylphenyl)-w-hydroxy

CAS No. 9064-13-5

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Skin Sens. 1 H317

**Triethylamine** 

CAS No. 121-44-8 EINECS no. 204-469-4

Concentration  $\Rightarrow$  0,1 < 1 %

Trade name: Clear Shield Canvas Guard Satin

Version: 3 / GB Date revised: 09.01.2015

Substance number: 3602XX413 Replaces Version: 2 / GB Print date: 09.08.18

Classification (Regulation (EC) No. 1272/2008)

 Skin Corr. 1A
 H314

 Flam. Liq. 2
 H225

 Acute Tox. 3
 H331

 Acute Tox. 3
 H311

 Acute Tox. 4
 H302

Concentration limits (Regulation (EC) No. 1272/2008)

STOT SE 3 H335 >= 1

#### Mixture of

alpha-3-(3-(2h-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyet hylene) and alpha-3-(3-(2h-benzotriazol-2-yl)-

5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2h-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

EINECS no. 400-830-7

Concentration >= 0,1 < 1 %

Classification (Regulation (EC) No. 1272/2008)

Skin Sens. 1 H317 Aquatic Chronic 2 H411

# Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl

**1,2,2,6,6-pentamethyl-4-piperidyl sebacate**Registration no. 01-2119491304-40

Concentration >= 0,25 < 1 %

Classification (Regulation (EC) No. 1272/2008)

Skin Sens. 1A H317 Aquatic Acute 1 H400 Aquatic Chronic 1 H410

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

#### After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

#### After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

# After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

# 4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

# 4.3. Indication of any immediate medical attention and special treatment needed

Trade name: Clear Shield Canvas Guard Satin

Version: 3 / GB Date revised: 09.01.2015

Substance number: 3602XX413 Replaces Version: 2 / GB Print date: 09.08.18

#### Hints for the physician / treatment

Treat symptomatically

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

#### Suitable extinguishing media

Recommended: alcohol resistant foam, CO2, powders, water spray/mist, Not be used for safety reasons: water jet

### 5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon dioxide (CO2); Carbon monoxide (CO); dense black smoke

# 5.3. Advice for firefighters

# Special protective equipment for fire-fighting

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

### 6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

#### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

# 6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

#### Advice on safe handling

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

#### Classification of fires / temperature class / Ignition group / Dust explosion class

Temperature class T4

# 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Store in accordance with national regulation

#### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

#### Further information on storage conditions

Store between 15 and 30 °C in a dry, well ventilated place. Keep container tightly closed. No smoking.

Trade name: Clear Shield Canvas Guard Satin

Version: 3 / GB Date revised: 09.01.2015

Substance number: 3602XX413 Replaces Version: 2 / GB Print date: 09.08.18

Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

# 7.3. Specific end use(s)

Liquid laminate

# SECTION 8: Exposure controls/personal protection \*\*\*

# 8.1. Control parameters

#### **Exposure limit values \*\*\***

Propane-1,2-diol

List EH40 Type OES

Value 10 mg/m<sup>3</sup>

Status: 2011

#### 8.2. Exposure controls

# **Exposure controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

### **Respiratory protection**

Not applicable.

#### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required.

Material thickness > 0,5 mm Breakthrough time < 30 min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

#### Eye protection

Use safety eyewear designed to protect against splash of liquids.

#### **Body protection**

Not applicable.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Form Liquid
Colour milky white
Odour mild

**Odour threshold** 

Remarks No data available

pH value

Remarks not determined

**Melting point** 

Trade name: Clear Shield Canvas Guard Satin

Version: 3 / GB Date revised: 09.01.2015

Substance number: 3602XX413 Replaces Version: 2 / GB Print date: 09.08.18

Remarks not determined

Freezing point

Remarks not determined

Initial boiling point and boiling range

Value appr. 100 °C

Pressure 1.013 hPa

Source Literature value

Flash point

Remarks Not applicable

**Evaporation rate (ether = 1):** 

Remarks not determined

Flammability (solid, gas)

Not applicable

**Upper/lower flammability or explosive limits** 

Lower explosion limit appr. 0,6 %(V)
Upper explosion limit appr. 20,4 %(V)

Source Literature value

Vapour pressure

Remarks not determined

Vapour density

Remarks not determined

**Density** 

Value appr. 0,97 g/cm<sup>3</sup>

Source calculated value

Solubility in water

Remarks miscible Partition coefficient: n-octanol/water

Remarks Not applicable

Ignition temperature

Value appr. 189 °C

Source Literature value

**Viscosity** 

Remarks

Remarks not determined

**Explosive properties** 

evaluation no

**Oxidising properties** 

evaluation None known

9.2. Other information

Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No hazardous reactions when stored and handled according to prescribed instructions.

# 10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

Trade name: Clear Shield Canvas Guard Satin

Version: 3 / GB Date revised: 09.01.2015

Substance number: 3602XX413 Replaces Version: 2 / GB Print date: 09.08.18

# 10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

# 10.5. Incompatible materials

No hazardous reactions when stored and handled according to prescribed instructions.

# 10.6. Hazardous decomposition products

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).

# SECTION 11: Toxicological information

# 11.1. Information on toxicological effects

#### **Acute dermal toxicity**

ATE > 2.000 mg/kg
Method calculated value (Regulation (EC) No. 1272/2008)

#### Acute inhalational toxicity

ATE > 20 mg/l

Administration/Form Vapors

Method calculated value (Regulation (EC) No. 1272/2008)
ATE > 5 mg/l

Administration/Form Dust/Mist

Method calculated value (Regulation (EC) No. 1272/2008)

#### **Aspiration hazard**

No special hazards have to be mentioned.

#### **Experience in practice**

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. May cause an allergic skin reaction. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### Other information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the GHS/CLP Regulation (EC) No 1272/2008.

# SECTION 12: Ecological information

# 12.1. Toxicity

# **General information**

There are no data available on the mixture itself.Do not allow to enter drains or water courses.The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

#### 12.2. Persistence and degradability

Trade name: Clear Shield Canvas Guard Satin

Version: 3 / GB Date revised: 09.01.2015

Print date: 09.08.18 Substance number: 3602XX413 Replaces Version: 2 / GB

#### General information

There are no data available on the mixture itself.

# 12.3. Bioaccumulative potential

#### **General information**

There are no data available on the mixture itself.

#### Partition coefficient: n-octanol/water

Remarks Not applicable

# 12.4. Mobility in soil

#### **General information**

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

#### General information

There are no data available on the mixture itself.

#### 12.6. Other adverse effects

#### **General information**

There are no data available on the mixture itself.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

# Disposal recommendations for the product

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is

EWC waste code 08 03 12\* waste ink containing dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

#### Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Not emptied containers are hazardous waste (waste code number 150110).

# **SECTION 14: Transport information**

#### Land transport ADR/RID

Non-dangerous goods

14.1. UN number

UN -

# 14.2. UN proper shipping name

# 14.3. Transport hazard class(es)

Class Label

14.4. Packing group

Packing group Transport category 0

14.5. Environmental hazards

Trade name: Clear Shield Canvas Guard Satin

Version: 3 / GB Date revised: 09.01.2015

Print date: 09.08.18 Substance number: 3602XX413 Replaces Version: 2 / GB

# Marine transport IMDG/GGVSee

The product does not constitute a hazardous substance in sea transport.

14.1. UN number

UN -

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Class Subsidiary risk

14.4. Packing group

Packing group

14.5. Environmental hazards

nο

# Air transport ICAO/IATA

The product does not constitute a hazardous substance in air transport.

14.1. UN number

UN -

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Class Subsidiary risk

14.4. Packing group

Packing group

14.5. Environmental hazards

#### Information for all modes of transport

# 14.6. Special precautions for user

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### Other information

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

nο

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC

VOC (EU) 6,27 60.9 % q/I

# Other information

The product does not contain substances of very high concern (SVHC).

# 15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

# **SECTION 16: Other information**

### Hazard statements listed in Chapter 3

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed. H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

Trade name: Clear Shield Canvas Guard Satin

Version: 3 / GB Date revised: 09.01.2015

Substance number: 3602XX413 Replaces Version: 2 / GB Print date: 09.08.18

H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

#### **CLP categories listed in Chapter 3**

Acute Tox. 3 Acute toxicity, Category 3
Acute Tox. 4 Acute toxicity, Category 4

Aquatic Acute 1 Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1 Hazardous to the aquatic environment, chronic, Category 1
Aquatic Chronic 2 Hazardous to the aquatic environment, chronic, Category 2

Flam. Liq. 2 Flammable liquid, Category 2
Skin Corr. 1A Skin corrosion, Category 1A
Skin Sens. 1 Skin sensitization, Category 1
Skin Sens. 1A Skin sensitization, Category 1A

#### Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: \*\*\* This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship. The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.