

## dream Scape

### Product Packaging

Each roll is meticulously packaged in a re-usable suspension box or ultra sturdy tube. **(No flat spots, no creases, no splices)**

*STD Lengths:* 75', 150', 300'  
*STD Widths:* 30", 48", 54", 60", 75"  
 (+/- 1/8")

*Core Diameter:* 3 inches i.d. Heavy-Duty  
 \*Custom lengths and widths available on request

### Physical Properties

*Product Weight:* 20oz. per lineal yd., ( 13oz. per sq. yd. )

*Vinyl Weight:* 17oz. per lineal yd.

*Fabric Weight:* 3oz. per lineal yd.

*Thickness:* 0.015 to 0.030 in.

\*depending on texture

*Fabric:* Poly-Cotton Osnaburg or Polyester Nonwoven

\*depending on texture

### Breaking Strengths, lbs. force

*Machine Direction-warp:*

\*Exceeds Type II minimum of 50lbs.

*Cross Machine Direction-fill:*

\*Exceeds Type II minimum of 55lbs.

### Tearing Strength, Scale

*Machine Direction-warp:*

\*Exceeds Type II minimum of 25lbs.

*Cross Machine Direction-fill:*

\*Exceeds Type II minimum of 25lbs

### Cold Crack Resistance @ 20° F

No Change

### Heat Aging ( 7 days at 158° F )

\*Does not become stiff, brittle, discolored, or show loss of grain

### Specifications/ Testing/ Certification

*Federal Specification:*

\*CCC-408-D,C,B,A \*Type II \*Class A

*CFFA Specification:*

\*CFFA-W-101-D \*Type II \*Class A

### Fire Testing

*ASTM-E84 Tunnel Test* Class A

*NFPA286 Corner Burn Test* Class A

*NFPA265 Corner Burn Test* Class A

*BS476 Part 6&7*

\*Meets or exceeds requirements for flame spread, smoke developments and flashover.

### Mold/Mildew/ Bacterial Resistance

*ASTM-G21 Specifications:* Passed all requirements of CCCW-408-D

### Environment

NYC MEA: Registered

\*Cadmium and Lead Free Formulation



dream it...print it...hang it...  
 dream it...print it...hang it...